



SMK NEW ENERGY

Hybrid Solar Inverter OEM/ODM Service Specialist



Shenzhen SMK New Energy Technology Co.,Ltd

Factory Add:3rd Floor,Block 49,Baigongao Industrial Park,Longhua District,Shenzhen,Guangdong China

Tel:+86-755 23768132

E-mail:info@smksolar.com

Whatsapp/Wechat:+86 135 2889 7663



www.smksolar.com

■ Shenzhen SMK New Energy Technology Co.,Ltd.All rights reserved.
Specifications subject to change without notice.

■ **SMK SOLAR** V3.5

ABOUT SMK

SMK Solar is a leading manufacturer of residential hybrid solar system products, we are dedicated to offering the most advanced solar inverter technology in the carbon-neutral era, to integrators, installers and end-users. Our products including the Hybrid Solar inverters, MPPT Solar Charge Controllers, Off grid inverters, Solar water heater, All in one solar generator etc. We are professional in residential stand-alone solar power solutions.

Over time, SMK solar has become one of the top hybrid solar inverter suppliers in the industry. Today, there are over 100000+ SMK systems installed all over the world, and the list is growing. Our platform offers the most accessible monitoring to all roles from the chain, products ranging from residential to commercial, service is always our first priority. We are committed to making our users benefit from the sun and enjoy life.

Shenzhen SMK Solar New Energy Technology Co., Ltd. always adheres to R & D investment and technological innovation, and provides customers with high-quality products and professional OEM / ODM services through mastering the core technology of photovoltaic system, strict control of quality management system and continuous improvement of after-sales service.

BUSINESS STRATEGY

SMK Solar has developed comprehensive product line for residential off grid system. We understand the need to offer choices for our customers and offer a range of technologies, price points and service. We align ourselves to brands that have the same value.

VISION STATEMENT

SMK Solar's vision remains being a true supplier partner that support you to be more competitive in you market and will always strive to offer excellent value and service.

MISSION

Make the use of green energy much easier and more convenient.

WHY SMK



Innovative

SMK solar is a leading manufacturer of solar inverter, solar water heater, mppt solar charger and various solar power products for several years.



Reliable

SMK Solar products designed by first-class R&D team and all products do 100% aging test and QC test before packing.



Professional

SMK Solar offer customized products with good performance and competitive price, we are dedicated to benefit our client continuously.

CONTENTS

Hybrid Solar Inverter

P
03-30

Portable Solar Power System

P
31-34

MPPT Solar Water Heating System

P
37-46

Charge Controller

P
47-50

Monitoring System

P
51-52

Project Application

P
53-54



Hybrid Solar Inverter

GM Series [On / Off- Grid Hybrid]

5.5 / 6.2KW 220 / 230Vac Output (PV 60-500Vdc)




Features

- Self-consumption and Feed-in to the grid
- Programmable multiple operation modes :Grid-tie , off-grid and grid-tie with backup
- Backflow prevention via external CT sensor and grid connection function
- Parallel operation up to 12 units in 1phase or 3phase
- Direct Plug WIFI Dongle Supported
- Output power factor 1.0
- High PV input voltage range 500Vdc Max
- Built-in MPPT solar controller 100 / 120A
- WiFi remote monitoring optional
- Detachable dust cover for harsh environment
- User-adjustable charging current and voltage
- Programmable supply priority for PV , Battery or Grid
- Support multiple output priority: SBU / SUB / SUF / ZEC
- EQ function to optimize battery performance and extend lifecycle



Bottom view





GM5500 - 48PL

GM6200 - 48PL

1. AC input
2. AC output
3. PV input
4. Battery input
5. Circuit breaker
6. Grounding
7. RS485 communication port
8. AC grid current sensor
9. Power on/off switch
10. RS232 communication port
- 11.Parallel communication port

System Diagram



Technical Data

MODEL	GM5500 - 48PL	GM6200 - 48PL
Phase	1-Phase In / 1-Phase Out	1-Phase In / 1-Phase Out
Maximum PV input power	5500W	6500W
Parallel Function	YES,12 Units	
Rated output power	5500VA / 5500W	6200VA/6200W
Lithium battery activation	Yes (By PV or Utility)	Yes (By PV or Utility)
Lithium battery communication	Yes	Yes
GRID-TIE OPERATION		
PV INPUT (DC)		
Nominal DC Voltage / Maximum DC Voltage	360VDC / 500VDC	
Start-up Voltage / Initial Feeding Voltage	150VDC / 120VDC	
MPPT Voltage Range	60VDC ~ 500VDC	60VDC~500VDC
Number of MPP Trackers / Maximum Input Current	1 / 18A	1/27A
GRID OUTPUT (AC)		
Nominal Output Voltage	220 / 230 / 240VAC	
Output Voltage Range	170-280VAC or 90-280VAC	
Nominal Output Current	22A	27A
Power Factor	0.6~1 (inductive or capacitive)	
Maximum Conversion Efficiency (DC/AC)	94%	
OFF-GRID OPERATION		
AC INPUT		
AC Start-up Voltage / Auto Restart Voltage	100Vac / 90Vac	
Acceptable Input Voltage Range	170-280VAC or 90-280VAC	
Maximum AC Input Current	40A	
PV INPUT (DC)		
Maximum DC Voltage	500VDC	
MPPT Voltage Range	60VDC~500VDC	60VDC~500VDC
Number of MPP Trackers / Maximum Input Current	1 / 18A	1/27A
BATTERY MODE OUTPUT (AC)		
Nominal Output Voltage	220/230/240VAC	
Output Waveform	Pure Sine wave	
Efficiency (DC to AC)	94%	
HYBRID OPERATION		
PV INPUT (DC)		
Nominal DC Voltage / Maximum DC Voltage	360VDC/500VDC	
Start-up Voltage / Initial Feeding Voltage	150VDC/120VDC	
MPPT Voltage Range	60VDC~500VDC	60VDC~500VDC
Number of MPPT Trackers / Maximum Input Current	1/18A	1/27A
GRID OUTPUT (AC)		
Nominal Output Voltage	220/230/240VAC	
Output Voltage Range	170-280VAC or 90-280VAC	
Nominal Output Current	22A	27A
AC INPUT		
AC Start-up Voltage / Auto Restart Voltage	100Vac/90Vac	
Acceptable Input Voltage Range	170-280VAC or 90-280VAC	
Maximum AC Input Current	40A	
BATTERY MODE OUTPUT (AC)		
Nominal Output Voltage	48VDC	
Efficiency (DC to AC)	94%	
BATTERY & CHARGER		
Nominal DC Voltage	48VDC	48VDC
Maximum Solar Charging Current	100A	120A
Maximum AC Charging Current	80A	80A
Maximum Charging Current	100A	120A
GENERAL		
PHYSICAL		
Dimension, D x W x H (mm)	448*315*122	450x300x130
Net Weight (kgs)	11	12
Communication Port	RS232+RS485+ External CT Port	
ENVIRONMENT		
Humidity	5%~95% Relative Humidity (Non-condensing)	
Operating Temperature	-10°C~55°C	

Product specifications are subject to change without further notice.

M Series [PV 60-500Vdc]
5.5KW 220V / 230Vac Output


Features



- Compatible work with lifepo4 battery via RS485
- Parallel operation up to 12 units in 1phase or 3phase
- Pure sine wave
- Power factor 1.0
- PV input 500Vdc Max
- Built-in MPPT 100A
- Capable to work without battery
- Detachable dust cover for harsh environment
- WiFi remote monitoring optional
- EQ function to optimize battery performance and extend lifecycle




Bottom view



1. AC input
2. AC output
3. PV input
4. Battery input
5. Circuit breaker
6. Grounding
7. RS485 communication port
8. Dry contact
9. Power on/off switch
10. RS232 communication port


System Diagram



Parallel 12 Units Max



Working Mode



Technical Data

MODEL	M5500-48PL
Capacity	5.5KVA/5.5KW
Parallel Capability	YES,12 Units
Lithium battery activation	NO
Lithium battery Communication	YES(RS485)
INPUT	
Nominal Voltage	230VAC
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280vac(For Home Appliances)
Frequency	50/60 Hz(Auto sensing)
OUTPUT	
Nominal Voltage	220/230VAC±5%
Surge Power	11000VA
Frequency	50/60Hz
Waveform	Pure Sine wave
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)
Peak Efficiency(PV to INV)	96%
Peak Efficiency(Battery to INV)	93%
Overload Protection	5s@>=140% load; 10s@110%~140% load
Crest Factor	3:1
Admissible Power Factor	0.6~1 (inductive or capacitive)
BATTERY	
Battery Voltage	48VDC
Floating Charge Voltage	54VDC
OverCharge Protection	63VDC
Charging Method	CC / CV
SOLAR CHARGER & AC CHARGER	
Solar Charger Type	MPPT
Max.PV Array Power	5500W
Max.PV Array Open Circuit Voltage	500VDC
PV Array MPPT Voltage Range	60VDC~500VDC
Max.Solar Input Current	18A
Max.Solar Charge Current	100A
Max.AC Charge Current	60A
Max.Charge Current	100A
PHYSICAL	
Dimensions,D x W x H(mm)	448x295x120
Package Dimensions,D x W x H(mm)	560x375x190
Net Weight(Kg)	10
Communication Interface	RS485/ RS232 / Dry-contact
ENVIRONMENT	
Operating Temperature Range	(-10°C to 55°C)
Storage Temperature	(-15°C ~ 60°C)
Humidity	5% to 95% Relative Humidity (Non-condensing)

Product specifications are subject to change without further notice.

M Series [PV 60-500Vdc]
6.2KW 220V / 230Vac Output



Features

- Compatible work with lifepo4 battery
- Parallel operation up to 12 units in 1phase or 3phase
- Direct Plug WIFI Dongle Supported - No additional cables required, just plug and play
- Pure sine wave
- Power factor 1.0
- PV input 500Vdc Max
- Built-in MPPT 120A
- Capable to work without battery
- Detachable dust cover for harsh environment
- WiFi remote monitoring optional
- Support multiple output priority: SUB,SBU,SUF
- EQ function to optimize battery performance and extend lifecycle




Bottom view




1. AC input
2. AC output
3. PV input
4. Battery input
5. Grounding
6. RS485 communication port
7. Power on/off switch
8. RS232 communication port
9. Parallel communication port

System Diagram



Parallel 12 Units Max



Technical Data

MODEL	M6200-48PL
Capacity	6.2KVA/6.2KW
Parallel Capability	YES,12 Units
Lithium battery activation	YES(By PV or Utility)
Lithium battery Communication	YES(RS485)
INPUT	
Nominal Voltage	230VAC
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280vac(For Home Appliances)
Frequency	50/60 Hz(Auto sensing)
OUTPUT	
Nominal Voltage	220/230VAC±5%
Surge Power	12400VA
Frequency	50/60Hz
Waveform	Pure Sine wave
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)
Peak Efficiency	94%
Overload Protection	5s@>= 140% load; 10s@110%~140% load
Crest Factor	3:1
Admissible Power Factor	0.6~1 (inductive or capacitive)
BATTERY	
Battery Voltage	48VDC
Floating Charge Voltage	54VDC
OverCharge Protection	63VDC
Charging Method	CC / CV
SOLAR CHARGER & AC CHARGER	
Solar Charger Type	MPPT
Max.PV Array Power	6500W
Max.PV Array Open Circuit Voltage	500VDC
PV Array MPPT Voltage Range	60VDC~500VDC
Max.Solar Input Current	27A
Max.Solar Charge Current	120A
Max.AC Charge Current	80A
Max.Charge Current	120A
PHYSICAL	
Dimensions,D x W x H(mm)	450*300*130
Package Dimensions,D x W x H(mm)	540x390x210
Net Weight(Kg)	12
Communication Interface	RS232 / RS485
ENVIRONMENT	
Operating Temperature Range	(-10°C to 55°C)
Storage Temperature	(-15°C ~ 60°C)
Humidity	5% to 95% Relative Humidity (Non-condensing)

Product specifications are subject to change without further notice.


M Series [PV 60-500Vdc]

8.5 / 11KW 220V / 230Vac Output




Features

- Dual AC output
- Built-in 2 MPPT
- Parallel max up to 6 units
- Lithium battery activation function by PV or Utility
- Compatible work with LiFePO4 battery via RS485
- Pure Sine Wave
- Power factor 1.0
- PV Input 500Vdc Max
- Built-in MPPT 140A/160A
- Capable to work without battery
- Detachable dust cover for harsh environment
- Wifi remote monitoring optional
- Support multiple output priority: SUB,SBU,SUF
- EQ function to optimize battery performance and extend lifecycle




Bottom view




1. Solar input - 1
2. Solar input - 2
3. AC input
4. Grounding
5. AC Main output
6. AC Second output
7. Dry contact
8. WiFi (Optional)
9. RS485 communication port
10. RS232 communication port
11. Parallel
12. Battery input
13. Power on / off switch

System Diagram



Parallel 6 Units Max



Technical Data

MODEL	M8500T-48PL	M11000T-48PL
CAPACITY	8.5KVA/8.5KW	11KVA/11KW
Maximum PV Input Power	10KW	11KW
Twin AC Output Function	YES	YES
Maximum Main Output Power	8.5KVA/8.5KW	11KVA/11KW
Maximum Second Output Power	5KVA/5KW	5KVA/5KW
Maximum Total Output Power	8.5KVA/8.5KW	11KVA/11KW
Parallel Capability	YES, 6units	YES, 6units
Lithium Battery Communication	YES(RS485)	YES(RS485)
Lithium Battery Activation	YES(By PV or Utility)	YES(By PV or Utility)
INPUT		
Nominal Voltage	230VAC	
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280VAC(For Home Appliances)	
Frequency	50/60 Hz (Auto sensing)	
OUTPUT		
Nominal Voltage	220/230/240VAC	
Surge Power	17000VA	22000VA
Frequency	50/60 Hz	
Waveform	Pure Sine wave	
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)	
Peak Efficiency (PV to INV)	96%	
Peak Efficiency (Battery to INV)	93%	
Overload Protection	5s@ > =140% load; 10s@110%~140% load	
Crest Factor	3:1	
Admissible Power Factor	0.6~1 (inductive or capacitive)	
Grid-tie Operation	NO	
BATTERY		
Battery Voltage	48VDC	48VDC
Maximum Discharge Current	180A	220A
Floating Charge Voltage	54VDC	54VDC
OverCharge Protection	63VDC	63VDC
Charging Method	CC/CV	CC/CV
Solar Charger & AC Charger		
Solar Charger TYPE	MPPT	MPPT
Max.PV Array Power	5000W*2	5000W*2
Max. PV Array Open Circuit Voltage	500VDC	500VDC
PV Array MPPT Voltage Range	60VDC~500VDC	60VDC~500VDC
Max. Solar Input Current	18A*2	18A*2
Max. Solar Charge Current	140A	160A
Max. AC Charge Current	120A	120A
Max. Charge Current	140A	160A
PHYSICAL		
Dimensions, D x W x H(mm)	540*415*122	540*415*122
Net Weight (Kgs)	14.5	15.5
Communication Interface	RS232/RS485/Dry-contact	RS232/RS485/Dry-contact
LCD	YES	YES
ENVIRONMENT		
Operating Temperature Range	-10°C to 55°C	
Storage temperature	-15°C~ 60°C	
Humidity	5% to 95% Relative Humidity (Non-condensing)	

Product specifications are subject to change without further notice.


EM Series [PV 60-500Vdc]

1.5 / 2.5 / 3.5 / 5.5 / 6.2KW 220V / 230Vac Output




Features

- Lithium battery activation function by PV or Utility
- Compatible work with lifepo4 battery via Rs485
- Pure sine wave
- Power factor 1.0
- PV input Voltage 60Vdc-500Vdc
- Built-in MPPT 60A / 100A /120A
- Capable to work without battery
- Detachable dust cover for harsh environment
- WiFi remote monitoring optional
- Support multiple output priority: UTL, SOL, SBU, SUB
- EQ function to optimize battery performance and extend lifecycle




Bottom view




1. AC input
2. AC output
3. PV input
4. Battery input
5. RS232 / RS485 communication port
6. Grounding
7. Power on/off switch

System Diagram



Working Mode



Technical Data

MODEL	EM1500-24L	EM2500-24L	EM3500-24L	EM5500-48L	EM6200-48L
Capacity	1.5KVA/1.5KW	2.5KVA/2.5KW	3.5KVA/3.5KW	5.5KVA/5.5KW	6.2KVA/6.2KW
Parallel Capability	NO	NO	NO	NO	NO
Lithium Battery activation	YES (By PV only)		YES (By PV or Utility)		
Lithium Battery communication	YES(RS485)				
INPUT					
Nominal Voltage	230VAC				
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280vac(For Home Appliances)				
Frequency	50/60 Hz(Auto sensing)				
OUTPUT					
Nominal Voltage	220/230VAC±5%				
Surge Power	3000VA	5000VA	7000VA	11000VA	12400VA
Frequency	50/60Hz				
Waveform	Pure Sine wave				
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)				
Peak Efficiency(PV to INV)	96%				
Peak Efficiency(Battery to INV)	93%				
Overload Protection	5s@>=140% load; 10s@110%~140% load				
Crest Factor	3:1				
Admissible Power Factor	0.6~1 (inductive or capacitive)				
BATTERY					
Battery Voltage	24VDC	24VDC	24VDC	48VDC	48VDC
Floating Charge Voltage	27VDC	27VDC	27VDC	54VDC	54VDC
OverCharge Protection	33VDC	33VDC	33VDC	63VDC	63VDC
Charging Method	CC / CV				
SOLAR CHARGER & AC CHARGER					
Solar Charger Type	MPPT				
Max.PV Array Power	2000W	3000W	4000W	5500W	6500W
Max.PV Array Open Circuit Voltage	500VDC				
PV Array MPPT Voltage Range	60VDC~500VDC				
Max.Solar Input Current	15A	15A	15A	18A	27A
Max.Solar Charge Current	60A	100A	100A	100A	120A
Max.AC Charge Current	60A	60A	80A	80A	80A
Max.Charge Current (PV+AC)	60A	100A	100A	100A	120A
PHYSICAL					
Dimensions,D x W x H(mm)	358*295*100	358*295*100	358*295*100	438*295*105	438*295*105
Package Dimensions,D x W x H(mm)	465*380*175	465*380*175	465*380*175	560*375*185	560*375*185
Net Weight(Kg)	6	6.5	7	9	9
Communication Interface	RS232+RS485				
ENVIRONMENT					
Operating Temperature Range	(-10℃ to 55℃)				
Storage Temperature	(-15℃ ~ 60℃)				
Humidity	5% to 95% Relative Humidity (Non-condensing)				

Product specifications are subject to change without further notice.


EXM Series [PV 60-500Vdc]

4.2KW 220V / 230Vac Output




Features

- Lithium battery activation function by PV or Utility
- Compatible work with lifepo4 battery via Rs485
- Pure sine wave
- Power factor 1.0
- PV input Voltage 60Vdc-500Vdc
- Built-in MPPT 100A
- Capable to work without battery
- Detachable dust cover for harsh environment
- WiFi remote monitoring optional
- Support multiple output priority: UTL, SOL, SBU, SUB,SUF
- EQ function to optimize battery performance and extend lifecycle




Bottom view



1. AC input
2. AC output
3. PV input
4. Battery input
5. RS232 / RS485 communication port
6. Grounding
7. Power on/off switch

System Diagram



Technical Data

MODEL	EXM4200-24L
Capacity	4.2KVA/4.2KW
Parallel Capability	NO
Lithium Battery activation	YES (By PV or Utility)
Lithium Battery communication	YES(RS485)
INPUT	
Nominal Voltage	230VAC
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280vac(For Home Appliances)
Frequency	50/60 Hz(Auto sensing)
OUTPUT	
Nominal Voltage	220/230VAC±5%
Surge Power	7000VA
Frequency	50/60Hz
Waveform	Pure Sine wave
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)
Peak Efficiency(PV to INV)	96%
Peak Efficiency(Battery to INV)	93%
Overload Protection	5s@ >= 140% load; 10s@ 110%~140% load
Crest Factor	3:1
Admissible Power Factor	0.6~1 (inductive or capacitive)
BATTERY	
Battery Voltage	24VDC
Floating Charge Voltage	27VDC
OverCharge Protection	33VDC
Charging Method	CC / CV
SOLAR CHARGER & AC CHARGER	
Solar Charger Type	MPPT
Max.PV Array Power	4500W
Max.PV Array Open Circuit Voltage	500VDC
PV Array MPPT Voltage Range	60VDC~500VDC
Max.Solar Input Current	15A
Max.Solar Charge Current	100A
Max.AC Charge Current	80A
Max.Charge Current (PV+AC)	100A
PHYSICAL	
Dimensions,D x W x H(mm)	358*295*105.5
Package Dimensions,D x W x H(mm)	465*375*175
Net Weight(Kg)	6.2
Communication Interface	RS232+RS485
ENVIRONMENT	
Operating Temperature Range	(-10℃ to 55℃)
Storage Temperature	(-15℃ ~ 60℃)
Humidity	5% to 95% Relative Humidity (Non-condensing)

Product specifications are subject to change without further notice.

EP Series [Plastic PV 60-500Vdc]
5.5KW 220V / 230Vac Output




Features

- Elegant plastic design.
- Compatible work with lifepo4 battery via RS485
- Lithium battery activation function, which can be triggered by PV
- Pure sine wave
- Power factor 1.0
- PV input Voltage 60Vdc-500Vdc
- Built-in MPPT 100A
- Capable to work without battery
- Detachable dust cover for harsh environment
- WiFi remote monitoring optional
- Support multiple output priority: UTL, SOL, SBU, SUB
- EQ function to optimize battery performance and extend lifecycle




Bottom view




1. AC input
2. AC output
3. PV input
4. Battery input
5. RS232 / RS485 communication port
6. Power on/off switch

System Diagram



Working Mode



Technical Data

MODEL	EP5500-48L
Capacity	5.5KVA/5.5KW
Parallel Capability	NO
Lithium Battery activation	YES (By PV only)
Lithium Battery communication	YES(RS485)
INPUT	
Nominal Voltage	230VAC
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280vac(For Home Appliances)
Frequency	50/60 Hz(Auto sensing)
OUTPUT	
Nominal Voltage	220/230VAC±5%
Surge Power	11000VA
Frequency	50/60Hz
Waveform	Pure Sine wave
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)
Peak Efficiency(PV to INV)	96%
Peak Efficiency(Battery to INV)	93%
Overload Protection	5s@ >= 140% load; 10s@ 110%~140% load
Crest Factor	3:1
Admissible Power Factor	0.6~1 (inductive or capacitive)
BATTERY	
Battery Voltage	48VDC
Floating Charge Voltage	54VDC
OverCharge Protection	63VDC
Charging Method	CC / CV
SOLAR CHARGER & AC CHARGER	
Solar Charger Type	MPPT
Max.PV Array Power	5500W
Max.PV Array Open Circuit Voltage	500VDC
PV Array MPPT Voltage Range	60VDC~500VDC
Max.Solar Input Current	18A
Max.Solar Charge Current	100A
Max.AC Charge Current	80A
Max.Charge Current	100A
PHYSICAL	
Dimensions,D x W x H(mm)	433*310*125.5
Package Dimensions,D x W x H(mm)	540*436*230
Net Weight(Kg)	7.6
Communication Interface	RS232+RS485
ENVIRONMENT	
Operating Temperature Range	(-10℃ ~ 55℃)
Storage Temperature	(-15℃ ~ 60℃)
Humidity	5% to 95% Relative Humidity (Non-condensing)

Product specifications are subject to change without further notice.

EM - T Series [PV 60-500Vdc]
6.2KW 220V / 230Vac Output




Features


- Dual output for smart load management
- Lithium battery activation function by PV or Utility
- Compatible work with LiFePO4 battery via RS485
- PV Input 500Vdc Max
- Built-in MPPT 120A
- Capable to work without battery
- Detachable dust cover for harsh environment
- Wifi remote monitoring optional
- Support multiple output priority: UTL,SOL,SBU,SUB
- EQ function to optimize battery performance and extend lifecycle



Bottom view



System Diagram



Technical Data

MODEL	EM6200T-48L
PHASE	1-Phase In /1-Phase Out
Maximum PV Input Power	6500W
Maximum Main Output Power	6200VA/6200W
Maximum Second Output Power	6200VA/6200W
Maximum Total Output Power	6200VA/6200W
Parallel Capability	NO
Lithium Battery activation	YES (By PV or Utility)
Lithium Battery communication	YES(RS485)
AC INPUT	
Nominal Voltage	230VAC
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280VAC(For Home Appliances)
Frequency	50/60 Hz (Auto sensing)
AC OUTPUT	
Nominal Voltage	220/230VAC±5%
Surge Power	12400VA
Frequency	50/60 Hz
Waveform	Pure Sine wave
Dual Outputs	Yes
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)
Peak Efficiency	94%
Overload Protection	5s@ > =140% load; 10s@100%~140% load
Admissible Power Factor	0.6~1 (inductive or capacitive)
BATTERY	
Battery Voltage	48VDC
Floating Charge Voltage	54VDC
OverCharge Protection	63VDC
Charging Method	CC/CV
SOLAR CHARGER & AC CHARGER	
Solar Charger TYPE	MPPT
Max.PV Array Power	6500W
Max. PV Array Open Circuit Voltage	500VDC
PV Array MPPT Voltage Range	60VDC~500VDC
Max. Solar Input Current	1 / 27A
Max. Solar Charge Current	120A
Max. AC Charge Current	80A
Max. Charge Current	120A
PHYSICAL	
Dimensions, D x W x H(mm)	438x312x122
Package Dimensions, D x W x H(mm)	540x390x210
Net Weight (Kgs)	11
Communication Interface	RS485(RJ45)/RS232(DB9)
ENVIRONMENT	
Operating Temperature Range	-10°C to 55°C
Storage temperature	-15°C~ 60°C
Humidity	5% to 95% Relative Humidity (Non-condensing)


Product specifications are subject to change without further notice.

EMT Pro Series [PV 30-500Vdc/PV 60-500Vdc]
3.6 / 6.2KW 220V / 230Vac Output


Features



- Dual output for smart load management
- Lithium battery activation function by PV or Utility
- Colored LCD with RGB lights
- Compatible work with LiFePO4 battery via RS485
- PV Input 500Vdc Max
- Built-in MPPT 100/120A
- Capable to work without battery
- Detachable dust cover for harsh environment
- Wifi remote monitoring optional
- Support multiple output priority: UTL, SOL, SBU, SUB, SUF
- EQ function to optimize battery performance and extend lifecycle




Bottom view



1. Second out
2. Main out
3. AC input
4. RS232 communication port
5. Grounding
6. RS485 communication port
7. Battery input
8. PV input

System Diagram



Technical Data

MODEL	EM3600T-24L Pro	EM6200T-48L Pro
PHASE	1-Phase In /1-Phase Out	1-Phase In /1-Phase Out
Maximum PV Input Power	4000W	6500W
Maximum Main Output Power	3600VA/3600W	6200VA/6200W
Maximum Second Output Power	3600VA/3600W	6200VA/6200W
Maximum Total Output Power	3600VA/3600W	6200VA/6200W
Parallel Capability	NO	NO
Lithium Battery activation	YES (By PV or Utility)	YES (By PV or Utility)
Lithium Battery communication	YES(RS485)	YES(RS485)
AC INPUT		
Nominal Voltage	230VAC	
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280VAC(For Home Appliances)	
Frequency	50/60 Hz (Auto sensing)	
AC OUTPUT		
Nominal Voltage	220/230VAC±5%	
Surge Power	7200VA	12400VA
Frequency	50/60 Hz	
Waveform	Pure Sine wave	
Dual Outputs	Yes	
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)	
Peak Efficiency	94%	
Overload Protection	5s@ > =140% load; 10s@110%~140% load	
Admissible Power Factor	0.6~1 (inductive or capacitive)	
BATTERY		
Battery Voltage	24VDC	48VDC
Floating Charge Voltage	27VDC	54VDC
OverCharge Protection	33VDC	63VDC
Charging Method	CC/CV	CC/CV
SOLAR CHARGER & AC CHARGER		
Solar Charger TYPE	MPPT	
Max.PV Array Power	4000W	6500W
Max. PV Array Open Circuit Voltage	500VDC	
PV Array MPPT Voltage Range	30VDC~500VDC	60VDC~500VDC
Max. Solar Input Current	1 / 15A	1 / 27A
Max. Solar Charge Current	100A	120A
Max. AC Charge Current	80A	80A
Max. Charge Current	100A	120A
PHYSICAL		
Dimensions, D x W x H(mm)	368x312x105.5	438x312x122
Package Dimensions, D x W x H(mm)	470x382x180	540x390x210
Net Weight (Kgs)	6.7	9.3
Communication Interface	RS485(RJ45)/RS232(DB9)	
LCD	Colorful Screen+RGB Light	
ENVIRONMENT		
Operating Temperature Range	-10°C to 55°C	
Storage temperature	-15°C~ 60°C	
Humidity	5% to 95% Relative Humidity (Non-condensing)	

Product specifications are subject to change without further notice.

EMT Pro Series [PV 60-500Vdc]
8.5 / 11KW 220V / 230Vac Output




Features

- Dual output for smart load management
- Built-in 2 MPPT
- Colored LCD with RGB lights
- Lithium battery activation function by PV or Utility
- Compatible work with LiFePO4 battery via RS485
- Pure Sine Wave
- Power factor 1.0
- PV Input 500Vdc Max
- Built-in MPPT 140A/160A
- Capable to work without battery
- Detachable dust cover for harsh environment
- Wifi remote monitoring optional
- Support multiple output priority: SUB,SBU,SUF
- EQ function to optimize battery performance and extend lifecycle




Bottom view



1. Solar input - 1
2. Solar input - 2
3. AC input
4. Grounding
5. Main output
6. Second output
7. Dry contact
8. WiFi(Optional)
9. RS485 communication port
10. RS232 communication port
11. Battery input
12. Power on / off switch

System Diagram



Technical Data

MODEL	EM8500T-48L Pro	EM11000T-48L Pro
Capacity	8.5KVA/8.5KW	11KVA/11KW
Maximum PV Input Power	10KW	11KW
Parallel Capability	NO	NO
Lithium Battery Activation	YES (By PV or Utility)	
Lithium Battery Communication	YES(RS485)	
INPUT		
Nominal Voltage	230VAC	
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280VAC(For Home Appliances)	
Frequency	50/60 Hz (Auto sensing)	
OUTPUT		
Nominal Voltage	220/230/240VAC	
Surge Power	17000VA	22000VA
Frequency	50/60 Hz	
Waveform	Pure Sine wave	
Dual Outputs	YES	
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)	
Peak Efficiency	94%	
Overload Protection	5s@ > =140% load; 10s@110%~140% load	
Admissible Power Factor	0.6~1 (inductive or capacitive)	
BATTERY		
Battery Voltage	48VDC	48VDC
Maximum Discharge Current	180A	220A
Floating Charge Voltage	54VDC	54VDC
OverCharge Protection	63VDC	63VDC
Charging Method	CC/CV	
SOLAR CHARGER & AC CHARGER		
Solar Charger TYPE	MPPT	MPPT
Max.PV Array Power	5000W*2	5500W*2
Max. PV Array Open Circuit Voltage	500VDC	500VDC
PV Array MPPT Voltage Range	60VDC~500VDC	60VDC~500VDC
Max. Solar Input Current	18A*2	18A*2
Max. Solar Charge Current	140A	160A
Max. AC Charge Current	120A	120A
Max. Charge Current	140A	160A
PHYSICAL		
Dimensions, D x W x H(mm)	540x403x122	540x403x122
Package Dimensions,D x W x H(mm)	637x495x214	637x495x214
Net Weight (Kgs)	14.5	14.8
Communication Interface	RS232/RS485/DRY CONTACT	
LCD	Colorful Screen+RGB Light	
ENVIRONMENT		
Operating Temperature Range	-10°C to 55°C	
Storage temperature	-15°C~ 60°C	
Humidity	5% to 95% Relative Humidity (Non-condensing)	

Product specifications are subject to change without further notice.

EM Series [PV 60-500Vdc]

8.5 / 11KW 220V / 230Vac Output




Features

- Built-in 2 MPPT
- Lithium battery activation function by PV or Utility
- Compatible work with LiFePO4 battery via RS485
- Pure Sine Wave
- Power factor 1.0
- PV Input 500Vdc Max
- Built-in MPPT 140A/160A
- Capable to work without battery
- Detachable dust cover for harsh environment
- Wifi remote monitoring optional
- Support multiple output priority: SUB,SBU,SUF
- EQ function to optimize battery performance and extend lifecycle




Bottom view



1. Solar input - 1
2. Solar input - 2
3. AC input
4. AC output
5. Grounding
6. Dry contact
7. WiFi(Optional)
8. RS485 communication port
9. RS232 communication port
10. Battery input
11. Power on / off switch

System Diagram



Technical Data

MODEL	EM8500-48L	EM11000-48L
Capacity	8.5KVA/8.5KW	11KVA/11KW
Maximum PV Input Power	10KW	11KW
Parallel Capability	NO	NO
Lithium Battery Activation	YES (By PV or Utility)	
Lithium Battery Communication	YES(RS485)	
INPUT		
Nominal Voltage	230VAC	
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280VAC(For Home Appliances)	
Frequency	50/60 Hz (Auto sensing)	
OUTPUT		
Nominal Voltage	220/230/240VAC	
Surge Power	17000VA	22000VA
Frequency	50/60 Hz	
Waveform	Pure Sine wave	
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)	
Peak Efficiency	94%	
Overload Protection	5s@ > =140% load; 10s@110%~140% load	
Admissible Power Factor	0.6~1 (inductive or capacitive)	
BATTERY		
Battery Voltage	48VDC	48VDC
Maximum Discharge Current	180A	220A
Floating Charge Voltage	54VDC	54VDC
OverCharge Protection	63VDC	63VDC
Charging Method	CC/CV	
SOLAR CHARGER & AC CHARGER		
Solar Charger TYPE	MPPT	MPPT
Max.PV Array Power	5000W*2	5500W*2
Max. PV Array Open Circuit Voltage	500VDC	500VDC
PV Array MPPT Voltage Range	60VDC~500VDC	60VDC~500VDC
Max. Solar Input Current	18A*2	18A*2
Max. Solar Charge Current	140A	160A
Max. AC Charge Current	120A	120A
Max. Charge Current	140A	160A
PHYSICAL		
Dimensions, D x W x H(mm)	540*415*122	540*415*122
Net Weight (Kgs)	14	15
Communication Interface	RS232/RS485/DRY CONTACT	
LCD	YES	
ENVIRONMENT		
Operating Temperature Range	-10°C to 55°C	
Storage temperature	-15°C~ 60°C	
Humidity	5% to 95% Relative Humidity (Non-condensing)	

Product specifications are subject to change without further notice.

CM-S Series [PV30-500Vdc]

1.5 / 2.5/3.5KW 220V / 230Vac Output




Features

- Lithium battery activation function, which can be triggered by PV
- Pure Sine Wave
- PV Input 500Vdc Max
- Built-in MPPT 60A-100A
- Detachable dust cover for harsh environment
- Wifi remote monitoring optional
- Support multiple output priority: UTL,SOL,SBU,SUB
- EQ function to optimize battery performance and extend lifecycle




Bottom view




1. AC input
2. AC output
3. PV input
4. Battery input
5. Grounding

System Diagram



Working Mode



Technical Data

MODEL	CM1500-12S	CM1500-24S	CM2500-24S	CM3500-24S
Capacity	1500VA/1500W	1500VA/1500W	2500VA/2500W	3500VA/3500W
Parallel Capability	NO	NO	NO	NO
Lithium Battery Activation	YES(By PV)	YES(By PV)	YES(By PV)	YES(By PV)
Lithium battery Communication	NO	NO	NO	NO
INPUT				
Nominal Voltage	230VAC			
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280VAC(For Home Appliances)			
Frequency	50/60 Hz (Auto sensing)			
OUTPUT				
Nominal Voltage	220/230VAC±5%			
Surge Power	3000VA	3000VA	5000VA	7000VA
Frequency	50/60 Hz			
Waveform	Pure Sine wave			
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)			
Peak Efficiency (PV to INV)	96%			
Peak Efficiency (Battery to INV)	93%			
Overload Protection	5s@ > =140% load; 10s@100%~140% load			
Crest Factor	3:1			
Admissible Power Factor	0.6~1 (inductive or capacitive)			
BATTERY				
Battery Voltage	12Vdc	24Vdc		
Floating Charge Voltage	13.5Vdc	27Vdc		
OverCharge Protection	16.5Vdc	32Vdc		
Charging Method	CC/CV			
SOLAR CHARGER & AC CHARGER				
Solar Charger TYPE	MPPT			
Max.PV Array Power	2000W	2000W	3000W	4000W
Max. PV Array Open Circuit Voltage	500VDC			
PV Array MPPT Voltage Range	30VDC~500VDC			
Max. Solar Input Current	15A			
Max. Solar Charge Current	100A	60A	100A	100A
Max. AC Charge Current	60A	60A	60A	60A
Max. Charge Current(AC+PV)	100A	60A	100A	100A
PHYSICAL				
Dimensions, D x W x H(mm)	330*278*98			
Package Dimensions, D x W x H(mm)	400*365*174			
Net Weight (Kgs)	3.8	3.8	3.95	3.95
Communication Interface	RJ45 For WiFi			
ENVIRONMENT				
Operating Temperature Range	-10°C to 55°C			
Storage temperature	-15°C~ 60°C			
Humidity	5% to 95% Relative Humidity (Non-condensing)			

Product specifications are subject to change without further notice.

CM-N Series [PV30-500Vdc]

1.5 / 2.5/3.5KW 220V / 230Vac Output


Features



- Inverter Wake-up Function
- Pure Sine Wave
- PV Input 500Vdc Max
- Built-in MPPT 60A-100A
- Detachable dust cover for harsh environment
- Wifi remote monitoring optional
- Support multiple output priority: UTL,SOL,SBU,SUB
- EQ function to optimize battery performance and extend lifecycle




Bottom view



1. AC input
2. AC output
3. PV input
4. Battery input
5. Grounding

System Diagram



Technical Data

MODEL	CM1500-12N	CM1500-24N	CM2500-24N	CM3500-24N
Capacity	1500VA/1500W	1500VA/1500W	2500VA/2500W	3500VA/3500W
Parallel Capability	NO	NO	NO	NO
Lithium Battery Activation	NO	NO	NO	NO
Lithium battery Communication	NO	NO	NO	NO
Inverter Wake-up Function	YES	YES	YES	YES
INPUT				
Nominal Voltage	230VAC			
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280VAC(For Home Appliances)			
Frequency	50/60 Hz (Auto sensing)			
OUTPUT				
Nominal Voltage	220/230VAC±5%			
Surge Power	3000VA	3000VA	5000VA	7000VA
Frequency	50/60 Hz			
Waveform	Pure Sine wave			
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)			
Peak Efficiency (PV to INV)	96%			
Peak Efficiency (Battery to INV)	93%			
Overload Protection	5s@ > =140% load; 10s@100%~140% load			
Crest Factor	3:1			
Admissible Power Factor	0.6~1 (inductive or capacitive)			
BATTERY				
Battery Voltage	12Vdc	24Vdc		
Floating Charge Voltage	13.5Vdc	27Vdc		
OverCharge Protection	16.5Vdc	32Vdc		
Charging Method	CC/CV			
SOLAR CHARGER & AC CHARGER				
Solar Charger TYPE	MPPT			
Max.PV Array Power	2000W	2000W	3000W	4000W
Max. PV Array Open Circuit Voltage	500VDC			
PV Array MPPT Voltage Range	30VDC~500VDC			
Max. Solar Input Current	15A			
Max. Solar Charge Current	100A	60A	100A	100A
Max. AC Charge Current	60A	60A	60A	60A
Max. Charge Current(AC+PV)	100A	60A	100A	100A
PHYSICAL				
Dimensions, D x W x H(mm)	330*278*98			
Package Dimensions, D x W x H(mm)	400*365*174			
Net Weight (Kgs)	3.8	3.8	3.95	3.95
Communication Interface	RJ45 For WiFi			
ENVIRONMENT				
Operating Temperature Range	-10°C to 55°C			
Storage temperature	-15°C~ 60°C			
Humidity	5% to 95% Relative Humidity (Non-condensing)			

Product specifications are subject to change without further notice.

CML Series [PV30-160Vdc]

1/2KW PV30-160Vdc




Features


- Lithium battery activation by PV & Utility
- Pure Sine Wave
- PV Input 160Vdc Max
- Built-in MPPT 30A
- Detachable dust cover for harsh environment
- Support multiple output priority: UTL,SOL,SBU
- EQ function to optimize battery performance and extend lifecycle



Bottom view



System Diagram



Technical Data

MODEL	CML1000-12	CML2000-24
Capacity	1000VA/1000W	2000VA/2000W
Parallel Capacity	NO	NO
Lithium Battery Activation	YES (AC & PV)	YES (AC & PV)
INPUT		
Nominal Voltage	230VAC	
Acceptable Voltage Range	170-280VAC(For personal Computer); 90-280VAC(For Home Appliances)	
Frequency	50/60 Hz (Auto sensing)	
OUTPUT		
Nominal Voltage	220/230VAC±5%	
Surge Power	2000VA	4000VA
Frequency	50/60 Hz	
Waveform	Pure Sine wave	
Transfer Time	10ms(For personal Computer); 20ms(For Home Appliances)	
Peak Efficiency (PV to BAT)	96%	
Peak Efficiency (Battery to INV)	93%	
Overload Protection	5s@ > =140% load; 10s@100%~140% load	
Crest Factor	3:1	
Admissible Power Factor	0.6~1 (inductive or capacitive)	
BATTERY		
Battery Voltage	12Vdc	24V
Floating Charge Voltage	13.5Vdc	27V
OverCharge Protection	15.5Vdc	31V
Charging Method	CC/CV	
Solar Charger & AC Charger		
Solar Charger TYPE	MPPT	
Max.PV Array Power	600W	1200W
Max. PV Array Open Circuit Voltage	160VDC	
PV Array MPPT Voltage Range	30VDC~160VDC	
Max. Solar Input Current	30	
Max. Solar Charge Current	40	40
Max. AC Charge Current	40	40
Max. Charge Current(AC+PV)	80	80
PHYSICAL		
Dimensions, D x W x H(mm)	358x295x105	
Package Dimensions, DxWxH(mm)	384*339*174	
Net Weight (Kgs)	3.5	3.8
ENVIRONMENT		
Operating Temperature Range	-10°C ~ 55°C	
Storage temperature	-15°C ~ 60°C	
Humidity	5% to 95% Relative Humidity (Non-condensing)	

Product specifications are subject to change without further notice.


EML Series [PV 30-160Vdc]

1.5 KW / 3.5KW 220V / 230Vac Output


Features



- Lithium battery activation function by PV or Utility
- Compatible work with lifepo4 battery via RS485
- Pure sine wave
- Power factor 1.0
- PV input Voltage 30Vdc~160Vdc
- Built-in MPPT 60A
- Detachable dust cover for harsh environment
- WiFi remote monitoring optional
- Support multiple output priority: UTL, SOL, SBU




Bottom view




1. AC input
2. AC output
3. PV input
4. Battery input
5. RS232 / RS485 communication port
6. Grounding
7. Power on/off switch

System Diagram



Working Mode



Technical Data

MODEL	EML1500-12L	EML3500-24L
Capacity	1.5KVA/1.5KW	3.5KVA/3.5KW
Parallel Capability	NO	NO
Lithium Battery activation	YES (By PV only)	YES (By PV or Utility)
Lithium Battery communication	YES(RS485)	YES(RS485)
INPUT		
Nominal Voltage	230VAC	
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280vac(For Home Appliances)	
Frequency	50/60 Hz(Auto sensing)	
OUTPUT		
Nominal Voltage	220/230VAC±5%	
Surge Power	3000VA	7000VA
Frequency	50/60Hz	
Waveform	Pure Sine wave	
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)	
Peak Efficiency(PV to INV)	96%	
Peak Efficiency(Battery to INV)	93%	
Overload Protection	5s@>=140% load; 10s@100%~140% load	
Crest Factor	3:1	
Admissible Power Factor	0.6~1 (inductive or capacitive)	
BATTERY		
Battery Voltage	12V	24VDC
Floating Charge Voltage	13.5V	27.0VDC
OverCharge Protection	14.1V	28.2VDC
Charging Method	CC / CV	
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	
Max.PV Array Power	900W	1500W
Max.PV Array Open Circuit Voltage	160VDC	160VDC
PV Array MPPT Voltage Range	30VDC~160VDC	30VDC~160VDC
Max.Solar Input Current	50A	50A
Max.Solar Charge Current	60A	60A
Max.AC Charge Current	80A	80A
Max.Charge Current(PV+AC)	120A	120A
PHYSICAL		
Dimensions,D x W x H(mm)	358x295x105.5	
Package Dimensions,D x W x H(mm)	465x380x175	
Net Weight(Kg)	6.00	7.00
Communication Interface	RS232/RS485	
ENVIRONMENT		
Operating Temperature Range	(-10°C to 55°C)	
Storage Temperature	(-15°C ~ 60°C)	
Humidity	5% to 95% Relative Humidity (Non-condensing)	

Product specifications are subject to change without further notice.



LVM Series [PV 60-500Vdc]

3 / 5KW 110V / 120Vac Output




Features

- Compatible work with lifepo4 battery via RS485
- Parallel operation with up to 12 units in 1phase/3phase / split phase
- Pure sine wave
- Power factor 1.0
- PV input 500Vdc Max
- Built-in MPPT 80A
- Capable to work without battery
- Detachable dust cover for harsh environment
- WiFi remote monitoring optional
- EQ function to optimize battery performance and extend lifecycle



Bottom view



1. AC input
2. AC output
3. PV input
4. Battery input
5. Circuit breaker
6. Grounding
7. RS485 communication port
8. Dry contact (Optional)
9. Power on/off switch
10. RS232 communication port



WiFi/GPRS



IOS / Android APP



Web

System Diagram

Single Phase L-N = 120V







3-Phase =208V



Split Phase L1-L2 = 240V



Working Mode



Technical Data

MODEL	LVM3000-48PL	LVM5000-48PL
Capacity	3KVA/3KW	5KVA/5KW
Parallel Capability	YES,12 Units	
Split phase operation	YES, need at least 2 units parallel	
Lithium Battery activation	NO	YES(By PV or Utility)
Lithium Battery communication	YES(RS485)	YES(RS485)
INPUT		
Nominal Voltage	110/120VAC	
Acceptable Voltage Range	95-140VAC(For personal Computer);65-140VAC(For Home Appliances)	
Frequency	50/60 Hz(Auto sensing)	
OUTPUT		
Nominal Voltage	110/120VAC±5%	
Surge Power	6000VA	10000VA
Frequency	50/60Hz	
Waveform	Pure Sine wave	
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)	
Peak Efficiency(PV to INV)	97%	
Peak Efficiency(Battery to INV)	93%	
Overload Protection	5s@>=140% load; 10s@110%~140% load	
Crest Factor	3:1	
Admissible Power Factor	0.6~1 (inductive or capacitive)	
BATTERY		
Battery Voltage	48VDC	
Floating Charge Voltage	54VDC	
OverCharge Protection	63VDC	
Charging Method	CC/CV	
Solar Charger & AC Charger		
Max.PV Array Power	5000W	6500W
Solar Charger Type	MPPT	
Max.PV Array Open Circuit Voltage	500VDC	
PV Array MPPT Voltage Range	60VDC~500VDC	
Max.Solar Input Current	18A	27A
Max.Solar Charge Current	80A	100A
Max.AC Charge Current	60A	60A
Max.Charge Current	80A	100A
PHYSICAL		
Dimensions,D x W x H(mm)	448x315x122	450x300x130
Package Dimensions,D x W x H(mm)	540x390x217	540x390x217
Net Weight(Kg)	10	12
Communication Interface	RS485/RS232/Dry-contact	
ENVIRONMENT		
Operating Temperature Range	-10℃ to 55℃	
Storage Temperature	-15℃ ~ 60℃	
Humidity	5% to 95% Relative Humidity(Non-condensing)	

Product specifications are subject to change without further notice.

DM Series [Detachable LCD]

3.5 / 5.5KW 220 / 230Vac Output (PV60-500Vdc)


Features



- Detachable LCD
- Pure sine wave
- Power factor 1.0
- PV input 500Vdc Max
- Built-in MPPT 100A
- Capable to work without battery
- Detachable dust cover for harsh environment
- WiFi remote monitoring optional
- Compatible work with lifepo4 battery
- Support multiple output priority: UTL, SOL, SBU, SUB
- Parallel operation up to 12 units in 1phase or 3phase
- EQ function to optimize battery performance and extend lifecycle




Bottom view




1. AC input
2. AC output
3. PV input
4. Battery input
5. Circuit breaker
6. Grounding
7. RS485 communication port
8. RS232 communication port


System Diagram



Parallel 12 Units Max



Working Mode



Technical Data

MODEL	DM3500-24	DM5500-48	DM5500-48PL
Capacity	3.5KVA/3.5KW	5.5KVA/5.5KW	5.5KVA/5.5KW
Parallel Capability	NO	NO	YES,12 Units
Lithium Battery activation	NO	NO	NO
Lithium Battery communication	YES(RS485)	YES(RS485)	YES(RS485)
INPUT			
Nominal Voltage	230VAC		
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280vac(For Home Appliances)		
Frequency	50/60 Hz(Auto sensing)		
OUTPUT			
Nominal Voltage	220/230VAC±5%		
Surge Power	7000VA	11000VA	11000VA
Frequency	50/60Hz		
Waveform	Pure Sine wave		
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)		
Peak Efficiency(PV to INV)	96%		
Peak Efficiency(Battery to INV)	93%		
Overload Protection	5s@>=140% load; 10s@110%~140% load		
Crest Factor	3:1		
Admissible Power Factor	0.6~1 (inductive or capacitive)		
BATTERY			
Battery Voltage	24VDC	48VDC	48VDC
Floating Charge Voltage	27VDC	63VDC	54VDC
OverCharge Protection	33VDC		63VDC
Charging Method	CC/CV		
SOLAR CHARGER & AC CHARGER			
Solar Charger Type	9000W		
Max.PV Array Power	4000W		5500W
Max.PV Array Open Circuit Voltage	500VDC		
PV Array MPPT Voltage Range	60VDC~500VDC		
Max.Solar Input Current	15A	100A	18A
Max.Solar Charge Current	100A	60A	100A
Max.AC Charge Current	60A	100A	60A
Max.Charge Current	100A		100A
PHYSICAL			
Dimensions,D x W x H(mm)	448x295x129		
Package Dimensions,D x W x H(mm)	540x390x217		
Net Weight(Kg)	9		10
Communication Interface	USB/RS232/Dry-contact	USB/RS232/Dry-contact	RS485/RS232/Dry-contact
ENVIRONMENT			
Operating Temperature Range	(-10°C to 55°C)		
Storage Temperature	(-15°C ~ 60°C)		
Humidity	5% to 95% Relative Humidity(Non-condensing)		

Product specifications are subject to change without further notice.


RM Series [PV 60-500Vdc]

3 KW PV 500Vdc 110 / 120Vac Output
5.5KW PV 500Vdc 220 / 230Vac Output


Features



- Pure sine wave
- Power factor 1.0
- PV input 500Vdc Max
- Built-in MPPT 100A
- Capable to work without battery
- Detachable dust cover for harsh environment
- WiFi remote monitoring optional
- Compatible work with lifepo4 battery
- Support multiple output priority: UTL, SOL, SBU, SUB
- Parallel operation up to 12 units in 1phase or 3phase
- EQ function to optimize battery performance and extend lifecycle




Bottom view




1. Power on/off switch
2. RS232 communication port
3. RS485 communication port
4. Dry contact (Optional)
5. Battery breaker
6. Battery input
7. AC input
8. AC output
9. PV input
10. Parallel communication port
11. Grounding

System Diagram



Working Mode



Technical Data

MODEL	LVRM3000 - 48PL	Rm5500 - 48PL
Capacity	3KVA/3KW	5.5KVA/5.5KW
Parallel Capability	YES,12 Units	
Lithium Battery communication	YES(RS485)	YES(RS485)
INPUT		
Nominal Voltage	230VAC	
Acceptable Voltage Range	170-280VAC(For personal Computer);90-280vac(For Home Appliances)	
Frequency	50/60 Hz(Auto sensing)	
OUTPUT		
Nominal Voltage	110/120VAC±5%	220/230VAC±5%
Surge Power	6000VA	11000VA
Frequency	50/60Hz	
Waveform	Pure Sine wave	
Transfer Time	10ms(For personal Computer);20ms(For Home Appliances)	
Peak Efficiency(PV to INV)	97%	
Peak Efficiency(Battery to INV)	93%	
Overload Protection	5s@>=140% load; 10s@110%~140% load	
Crest Factor	3:1	
Admissible Power Factor	0.6~1 (inductive or capacitive)	
BATTERY		
Battery Voltage	48VDC	48VDC
Floating Charge Voltage	53VDC	54VDC
OverCharge Protection	63VDC	63VDC
Charging Method	CC / CV	
SOLAR CHARGER & AC CHARGER		
Solar Charger Type	MPPT	
Max.PV Array Power	5000W	5500W
Max.PV Array Open Circuit Voltage	500VDC	
PV Array MPPT Voltage Range	60VDC~500VDC	
Max.Solar Input Current	18A	18A
Max.Solar Charge Current	80A	100A
Max.AC Charge Current	60A	60A
Max.Charge Current	80A	100A
PHYSICAL		
Dimensions,D x W x H(mm)	130x438x438	
Package Dimensions,D x W x H(mm)	220x520x550	
Net Weight(Kg)	10	10
Communication Interface	RS485/ RS232 / Dry-contact	RS485/ RS232 / Dry-contact
ENVIRONMENT		
Operating Temperature Range	(-10℃ to 55℃)	
Storage Temperature	(-15℃ ~ 60℃)	
Humidity	5% to 95% Relative Humidity (Non-condensing)	

ESS - V Series [Portable Solar Power System]
1KW-3KW

Features




- Inbuilt LifePO4 lithium battery, High energy storage and longer life
- Double protection both BMS and charger
- Pure sine wave solar inverter, Friendly for electricity appliances
- Multiple DC output ports, Support charging different devices simultaneously
- Integrated solar power station (except solar panel),with handlebars and wheels,Portable
- Intelligent temperature cooling fan, Work silently
- All in one; integrated inverter/MPPT controller/battery into one
- Multiple charging methods
- LCD Display



System Diagram



Working Mode



Technical Data

MODEL		ESS-V1000	ESS-V1500	ESS-V2000	ESS-V3000
Installation Type		Portable			
Battery Voltage		25.6V			
Lithium Battery activation		YES(By PV or Utility)	YES(By PV or Utility)	YES(By PV or Utility)	YES(By PV or Utility)
Lithium Battery communication		YES(RS485)	YES(RS485)	YES(RS485)	YES(RS485)
INVERTER					
Rated Power		1000W	1500W	2000W	3000W
AC Input	Mains Charging Current	30A	30A	40A	60A
	Input Voltage Range	90-280V			
	Input Frequency	45-65Hz			
AC Output	Output Voltage	230Vac			
	Output Frequency	50/ 60Hz			
	Output Wave	Pure Sine Wave			
Inbuilt Lifepo4 Battery Capacity		1280WH LifePO4	1536WH LifePO4	2048WH LifePO4	3072WH LifePO4
SOLAR INPUT					
Max. PV Power		1000W	1000W	1500W	1500W
Range of Charging Voltage		30-160VDC	30-160VDC	30-160VDC	30-160VDC
Max Charge Current		40A	40A	60A	60A
Voltage For Floating Charge		29.0V			
DC OUTPUT					
Low Voltage Recovery Voltage		26.8VDC			
low Voltage Protection Voltage		22.4VDC			
5VDC USB Output Ports		2 * USB 2.0 5VDC 2.4A(MAX)			
TYPE C Output Ports		2 * Type C (5V3A/9V2A)			
12VDC Output Ports		2* MAX 4A			
PHYSICAL					
Heat dissipation/cooling		Temperature control by intelligent exhaust fan			
Display		Digital LCD+LED			
External Size		430*215*500	430*215*500	430*215*600	430*215*600
Packge Size		506*285*570	506*285*570	500*285*670	500*285*670
N.W (Net Weight)		21	23.2	33.7	44.2
G.W(Gross Weight)		23	34.5	35	46
ENVIRONMENT					
Operating Temperature Range		-10℃ ~ 55℃			
Storage Temperature		-15℃ ~ 60℃			
Humidity		5% to 95% Relative Humidity(Non-condensing)			

Product specifications are subject to change without further notice.

ESS - H Series [Portable Solar Power System]
2KW-3KW

Features




- Inbuilt LifePO4 lithium battery, High energy storage and longer life
- Double protection both BMS and charger
- Pure sine wave solar inverter, Friendly for electricity appliances
- Multiple DC output ports, Support charging different devices simultaneously
- Integrated solar power station (except solar panel)
- Wall mounted design
- Intelligent temperature cooling fan, Work silently
- All in one; integrated inverter/MPPT controller/battery into one
- Multiple charging methods
- LCD Display




System Diagram

Portable Solar Power System



Working Mode



Technical Data

MODEL		ESS-H2000	ESS-H3000
Installation Type		Wall mounted	
Battery Voltage		25.6V	
Lithium Battery activation		YES(By PV or Utility)	YES(By PV or Utility)
Lithium Battery communication		YES(RS485)	YES(RS485)
INVERTER			
Rated Power		2000W	3000W
AC Input	Mains Charging Current	40A	60A
	Input Voltage Range	90-280V	
	Input Frequency	45-65Hz	
AC Output	Output Voltage	230Vac	
	Output Frequency	50/ 60Hz	
	Output Wave	Pure Sine Wave	
Inbuilt Lifepo4 Battery Capacity		2048WH LifePO4	3072WH LifePO4
SOLAR INPUT			
Max. PV Power		1500W	1500W
Range of Charging Voltage		30-160VDC	30-160VDC
Max Charge Current		60A	60A
Voltage For Floating Charge		29.0V	
DC OUTPUT			
Low Voltage Recovery Voltage		26.8VDC	
low Voltage Protection Voltage		22.4VDC	
5VDC USB Output Ports		2 * USB 2.0 5VDC 2.4A(MAX)	
TYPE C Output Ports		2 * Type C (5V3A/9V2A)	
12VDC Output Ports		2* MAX 4A	
PHYSICAL			
Heat dissipation/cooling		Temperature control by intelligent exhaust fan	
Display		Digital LCD+LED	
External Size		430*215*550	430*215*550
Packge Size		500*325*620	500*325*620
N.W (Net Weight)		33.7	43.2
G.W(Gross Weight)		35	45
ENVIRONMENT			
Operating Temperature Range		-10℃ ~ 55℃	
Storage Temperature		-15℃ ~ 60℃	
Humidity		5% to 95% Relative Humidity(Non-condensing)	

Product specifications are subject to change without further notice.




MPPT Solar Water Heating System

MPPT Solar Water Heating Controller
SWHC-3K/4K Max (IP65)


Features



- Maximum power point tracking technology (MPPT Technology)
- Advanced DSP control chip, smart control
- Solar heating priority, automatic grid switching when solar insufficient
- IP65 Design, indoor and outdoor applications
- Water Temperature Detection
- The highest water temperature setting for grid heating and PV heating
- Manual Grid Heating Switch
- WiFi monitoring




Bottom view



1. WiFi monitoring
2. Temperature Sensor
3. PV input
4. AC output
5. AC input

System Diagram



Technical Data

Model	SWHC-3K MAX	SWHC-4K MAX
Scope of application	The MPPT water heating controller is only suitable for heating resistance heating components through solar power, and the controller load can only be used to connect resistance equipment or AC heaters with AC grid heating power within 230V/4000 watts.	The MPPT water heating controller is only suitable for heating resistance heating components through solar power, and the controller load can only be used to connect resistance equipment or AC heaters with AC grid heating power within 230V/4000 watts.
Photovoltaic characteristics		
Solar Max. input power	3000W	4000 W
Solar input current	≤ 15 A	≤ 20 A
Solar input voltage range	115Vdc-300Vdc	160 Vdc ~ 350 Vdc
MPPT operating voltage range	90Vdc-280Vdc	120 Vdc ~ 340 Vdc
MPPT efficiency	> 99%	
Solar heating output voltage range	0 ~ 260 Vac	
Solar heating output current range	≤ 15A	≤ 20 A
AC characteristics		
AC heating rated power	4000 W	4000 W
AC rated voltage	230 Vac	
AC working voltage range	180 Vac ~ 260 Vac	
AC rated current	≤20 A	≤20 A
Load requirement		
Load	load ≤ 230V/3000W the resistance value > 13 ohms	load ≤ 230V/4000W the resistance value > 13 ohms
Machine characteristics		
LCD Display	YES	
Max Water temperature	Settable (30-80°C)	
WIFI	YES	
Temperature sensor	YES(4M)	
Machine dimensions	250*155*75mm	250*155*80 mm
Package dimensions	290*250*120 mm	290*250*120 mm
Net weight	2.8KG	3 KG
Gross weight	3.4KG	3.6 KG
Ingress Protection	IP65	

Product specifications are subject to change without further notice.

MPPT Solar Water Heating Controller

SWHC-4K (IP65)



Features

- Maximum power point tracking technology
- Efficiency>99%
- Advanced DSP control chip, smart control
- High voltage 350Vdc Max
- Low energy consumption
- Low temperature working
- IP65 design




Detail view



1. Solar heating indicator
2. AC heating indicator
3. Fault indicator
4. Power indicator
5. PV input
6. AC output
7. AC input

System Diagram



Technical Data

MODEL	SWHC-4K
Scope of application	The MPPT water heating controller is only suitable for heating resistive load through solar power, and the controller can only be used to connect resistive equipment or AC water heaters with utility heating power within 230V/4000 watts.
PHOTOVOLTAIC CHARACTERISTICS	
Solar Max. input power	4000 W
Solar input current	≤ 20 A
Solar input voltage range	160 Vdc ~ 350 Vdc
MPPT operating voltage range	120 Vdc ~ 340 Vdc
MPPT efficiency	>99%
Solar heating output voltage range	0 Vac ~ 260 Vac
Solar heating output current range	≤ 20 A
AC CHARACTERISTICS	
AC heating rated power	4000 W
AC rated voltage	230 Vac
AC working voltage range	180 Vac ~ 260 Vac
AC rated current	≤20A
LOAD REQUIREMENT	
Load	load ≤ 230V/4000W the resistance value > 13 ohms
MACHINE CHARACTERISTICS	
Machine dimensions	255*201*95 mm
Package dimensions	363*272*170 mm
Net weight	3 KG
Gross weight	3.6 KG
Ingress Protection	IP65

Product specifications are subject to change without further notice.


MPPT Solar Water Heating Controller

SWHC-4K Pro (IP33)

Features



- Maximum power point tracking technology(MPPT Technology)
- Advanced DSP control chip , smart control
- Solar heating priority, automatic grid switching when solar insufficient
- Water Temperature Detection
- The highest water temperature setting for grid heating and pv heating
- ManualGrid Heating Switch




Bottom view



- 1.AC Input
- 2.AC Output
- 3.Temperature Sensor
- 4.PV Input

System Diagram



Technical Data

MODEL	SWHC-4K Pro
Scope of application	The MPPT water heating controller is only suitable for heating resistive load through solar power, and the controller can only be used to connect resistive equipment or AC water heaters with utility heating power within 230V/4000 watts.
PHOTOVOLTAIC CHARACTERISTICS	
Solar Max. input power	4000 W
Solar input current	≤ 20 A
Solar input voltage range	160 Vdc ~ 350 Vdc
MPPT operating voltage range	120 Vdc ~ 340 Vdc
MPPT efficiency	>99%
Solar heating output voltage range	0 Vac ~ 260 Vac
Solar heating output current range	≤ 20 A
AC CHARACTERISTICS	
AC heating rated power	4000 W
AC rated voltage	230 Vac
AC working voltage range	180 Vac ~ 260 Vac
AC rated current	≤20A
LOAD REQUIREMENT	
Load	load ≤ 230V/4000W the resistance value > 13 ohms
MACHINE CHARACTERISTICS	
Machine dimensions	195*182*57 mm
Package dimensions	255*246*158 mm
Net weight	2.4 KG
Gross weight	2.75 KG
Ingress Protection	IP33


Product specifications are subject to change without further notice.

MPPT Solar Water Heating Controller
SWHC-2K (IP21)


Features



- MPPT efficiency> 99%
- Built in DSP chip, smart control
- Multi- working models to cut the bill
- Wide range PV voltage put 35 Vdc~160 Vdc
- Low consumption and work at low temperature
- WIFI monitoring and remotely setting. (Optional)




Bottom view



1. Water Level
2. Water Temp
3. EPO
4. PV input
5. PV Load
6. Water Pump
7. PV Load
8. AC input

System Diagram



Technical Data

Model	SWHC-2K
Scope of application	Photovoltaic heating controllersare only suitable for heating bysolar power generation, and thecontroller load can only beconnected to heating rods withresistance properties
Characteristics Photovoltaic	
SolarMax.inputpower	2000W
Solar input current	≤18A
Solar input voltage range	40Vdc ~ 160Vdc
MPPT operating voltage range	35Vdc ~ 155Vdc
MPPT efficiency	>99%
Solar heating output voltage range	0 ~ 120Vdc
Solar heating output current range	≤18A
AC characteristics	
AC heating rated power	2000W
AC rated voltage	220Vac
AC working voltage range	180 ~ 270Vac
AC rated current	≤10A (The maximum current capacity of the controller should be considered when selecting the heating rod, if the AC output has no over current protection)
Machine characteristics	
Temperature adjustment range	50 ~ 80℃
Leakage action current	≤10MA
Leakage action time	≤0.1S
Protective function	Leakage protection,over-temperature protection, emergency shutdown,AC outputover-voltage protection, solar output over-voltage protection
Add water function	To add water automatically or manually, and the current of the water pump does not exceed AC 5A
Monitoring function	WiFi Monitoring (Optional)
Dimensions	250*155*80mm
Package dimensions	290*250*120mm
Net weight	1.8Kg
Gross weight	2.2Kg
Ingress Protection	IP21

Product specifications are subject to change without further notice.

MPPT Solar Water Heating System

SWH-H Series 50L 60L 80L




Features

- Photovoltaic power generation, low consumption and work at low temperature
- MPPT controller technology, 99% of efficiency maximum the solar power harvest and convert to heat
- Smart switching DC/AC control to cut the bill
- Pressurized water tank, with 24H continuous hot water output, without waste of cold water
- WIFI monitoring and remotely setting
- Easy installation, maintenance and commissioning



System Diagram



Component



Technical Data

MODEL	SWH-H50L	SWH-H60L	SWH-H80L
Volume	50L	60L	80L
SOLAR			
Solar Max output power	1200w		
Recommeded solar panel	500w	600w	800w
Heating time 40°C		4 Hours	
Annual solar Power Harvest	730 KWH	876 KWH	1168 KWH
Solar input voltage	160Vdc Max/25°C		
MPPT range	30Vdc-155Vdc		
AC			
AC heater power	2000w		
AC voltage	220v		
PHYSICAL			
Monitoring	WIFI setting and monitoring (Optional)		
Protection	Over temperture protection , leakage protection		
Inner tank material	Enamel		
Tank dimension	Φ390×785	Φ390×900	Φ440×835
Package dimension	530×440×915	530×440×1030	555×495×965
Net weight	19kg	21.5kg	25.3kg
Gross weight	20kg	23kg	28kg

Product specifications are subject to change without further notice.

Battery charge controller

5120W100AAC Charger 48Vdc


Features



- Charging super fast
- Smart to trigger Generator to charge through dry contact
- User friendly, no wiring design
- Clean power to charge battery
- Builtin DC breaker




Bottom view



- 1. Battery quick connector
- 2. Dry contact/BMS ports
- 3. AC quick connector

System Diagram



Technical Data

AC MODEL	ACC5120-48L
Max Charging Current	100Amp
AC Input Voltage	90-264VAC
AC Frequency	50/60Hz
Nominal battery Voltage	48Vdc (43-57dc adjustable)
Rated Power	5120W
Max Efficiency	94%
GENERAL SPECIFICATIONS	
Communication port	RS485(RJ45)+ DRY CONTACT(RJ11)
Operating TemperatureRange	-10°C to 55°C
Storage temperature	-15°C~ 60°C
Humidity	5% to 95% Relative Humidity (Non-condensing)
Ingress Protection	IP21
Dimension(D*W*H), mm	332x122x125
Net Weight, kg	5.9

Product specifications are subject to change without further notice.

MPPT Solar Charge Controller

SCH Series 30A-100A 12V/24V/36V/48V

Features




- 12V/24V/36V/48V Auto work, parallel design
- Multi-stage charging optimizes battery performance
- MPPT efficiency >99.5%, Peak conversion efficiency 98.5%
- Wide range Solar PV voltage input 18V~150Vdc
- Compatible with Gel, AGM, Flooded, Sealed lead acid and Lithium battery
- Multi-function LCD+LED display, system information intuitively
- Comprehensive protection
- Excellent heatsink cooling design, quiet operation
- Comfortable installation and commissioning
- Monitoring your system online via RS485 communication

Bottom view



1. RS485 communication port
2. PV input
3. Battery input
4. Load input
5. Temperature Sensor

System Diagram



Technical Data

MODEL	SCH 30A	SCH 40A	SCH 50A	SCH 60A	SCH 70A	SCH 80A	SCH 90A	SCH 100A
Solar System Voltage	12V/24V/36V/48V Auto work							
ELECTRICAL								
PV Operating Voltage	18-150Vdc@12V 35-150Vdc@24V 50-150Vdc@36V 65-150Vdc@48V							
Max. PV Input Power	12V 400W	12V 600W	12V 700W	12V 900W	12V 1000W	12V 1200W	12V 1300W	12V 1400W
	24V 800W	24V 1200W	24V 1400W	24V 1800W	24V 2800W	24V 2300W	24V 2600W	24V 2800W
	36V 1300W	36V 1700W	36V 2200W	36V 2600W	36V 3000W	36V 3300W	36V 3800W	36V 4200W
	48V 1700W	48V 2300W	48V 2900W	48V 3400W	48V 4000W	48V 4600W	48V 5000W	48V 5400W
Rated Output Current	30A	40A	50A	60A	70A	80A	90A	100A
Rated DC Load Current	40A		60A					
Self Consumption	<2W		<3W					
Max.Conversion Efficiency	97.5%		98.5%					
Protection	PV array short circuit, over charging,battery reverse polarity,output short circuit							
BATTERY CHARGING								
Battery Type	Sealed Gel/AGM Flooded Lithium Battery							
Charge Algorithm	3 stage: Bulk, Absorption, Float charging		4 stage: Bulk, Absorption, Float charging					
Bulk Charge Voltage	Sealed: 14.4V AGM 14.2V Gel:14.2V Flooded:14.6V User defined:10-15V							
Float Charge Voltage	Sealed/Gel/AGM:13.8V Flooded:13.7V User defined:10-15V							
Equalize Charge Voltage	N/A		Sealed:14.6V AGM:14.8V Flooded:14.9V					
Load Disconnect Voltage	9V-12V Adjustable							
Load reconnect voltage	Disconnect voltage +2V							
Temperature Compensation	5mV/℃ /2V with BTS							
COMMUNICATION								
Communication Port	Rs485 with On line monitoring system							
PHYSICAL								
Net Weight	3.3kg	3.3kg	6.5kg	6.5kg	7.8kg	7.8kg	9.0kg	9.0kg
Gross Weight	4.0kg	4.0kg	7.3kg	7.3kg	8.7kg	8.7kg	10kg	10kg
Dimension(mm)	220*170*90		310*230*110		370*230*110		405*230*110	
Cooling	Heatsink cooling							
Enclosure	IP 45							
ENVIRONMENT								
Ambient operating temperature	-25℃~60℃							
Storage Temperature	-40℃~80℃							
Humidity	5%-95% non-condensing							

※ Technical data for 12V system at 25℃, twice in 24V system rate, triple in 36V System rate and quadruple in 48V system rate.

Monitoring System


Wi-Fi Plug Pro / GRPS Plug Pro / 4G Plug Pro

Plug gable data logger can support Wi-Fi, GPRS, 4G, NB-IOT and other communication modes. Through DB9,RJ-45 and other connection modes, it is perfectly compatible with inverter, energy storage system, It can support the remote control, remote debugging, remote upgrading and other functions of the device, and can view the working status and power generation of the device in real time, so as to provide users with a complete remote, low-cost and visual monitoring solution.



Energy Storage Management Platform

Energy storage management platform, provides users with application services such as data collection, analysis, calculation, storage, alarm push, etc. Users can view the data of energy storage device through PC web page and mobile APP interface, and operate under the guidance of truly demand and voltage regulation.



DessMonitor



iOS



Android

Technical Data

Product Model	Wi-Fi Plug Pro	GPRS Plug Pro	4G Plug Pro
Product picture			
ESSENTIAL PARAMETERS			
Dimensions	51*45*27mm	51*45*27mm	51*45*27mm
Weight	60g	60g	60g
Protection class	IP65	IP65	IP65
Installation mode	Fixed to the equipment via screws	Fixed to the equipment via screws	Fixed to the equipment via screws
Rated voltage	DC 5~12V	DC 5~12V	DC 5~12V
Maximum current	800mA(5V)	2A(5V)	2A(5V)
External port	Db9/Aviation joint/RJ-45	Db9/Aviation joint/RJ-45	Db9/Aviation joint/RJ-45
Indicator lights	4	4	4
Operation temperature	-30°C~+85°C	-30°C~+85°C	-30°C~+85°C
Storage temperature	-40°C~+90°C	-40°C~+90°C	-40°C~+90°C
COMMUNICATION PARAMETERS			
Local communication	RS-232/RS-485/TTL	RS-485/RS-232/TTL	RS-485/RS-232/TTL
Public network access	Wi-Fi	GPRS	GPRS/TD-SCDMA/WCDMA/LTE
Baud rate	9600bps (default)	9600bps (default)	9600bps (default)
Working frequency	2.412GHz~2.484GHz	EGSM900/GSM880/DCS1800/PCS1900	FDD LTE:B1/B3/B8 TDD LTE:B38/B39/B40/B41 TDSCDMA:B34/B39 WCDMA:B1/B8 GSM:900/1800
Communication standard	IEEE802.11b/g/n	GPRS multi-slot class 10 IS-95A/B IS-2000	LTE-Advanced/WirelessMAN-Advanced(802.16m)
Maximum transmission rate	72Mbps	85.6Kbps	150Mbps
Communication distance	100m (open environment)	Carrier network	Carrier network
Antenna gain	2.7dBi	2.5dBi	2.5dBi
Antenna	External antenna(extend antenna optional)	External antenna(extend antenna optional)	External antenna(extend antenna optional)
SIM card	--	Nano card or chip card	Nano card or chip card
OTHER PARAMETERS			
Watchdog	Software watchdog +hardware watchdog	Software watchdog +hardware watchdog	Software watchdog +hardware watchdog
Device layer communication protocol	Modbus-RTU	Modbus-RTU	Modbus-RTU
Networking layer communication protocol	Modbus-TCP	Modbus-TCP	Modbus-TCP
Parameters setting mode	Massage/remote server	Massage/remote server	Massage/remote server
Firmware update mode	Remote server	Remote server	Remote server
Number of connected devices	1	1	1

Product specifications are subject to change without further notice.

Solutions

SMK Solar aim to be your best supplier of off grid solar system.

Solar solutions for everyone, everywhere

Off grid inverter 1KW-11KW
Energy storage system 1kwh-15kwh
Solar water heating system 2 / 3 / 4KW

Marketing

SMK Solar are active in global solar exhibitions.



Certifications



Project Application